



Technical changes reserved.
All WEBOMATIC machines comply with the valid
European regulations according to CE, EMC, EAC.

SuperMax-i

The classic beneath the WEBOMATIC single chamber machines gains not only technical improvements, but also a revival in terms of design and control. Designed after the WEBOMATIC CleanDesign®ed duoMAT-series, the SuperMax-i adaptes an IGT-control. The IGT-*standard* is equipped with two language sets, regulates the sealing and cutting times and can be supplied with up to 10 programs. The sealing bars are easy to extract by hand – like in the duoMAT-series without any tools needed.

Sales launch from 1.8.2015

Technical Data

Machine size	780 x 760 x 962 mm (W x D x H)
Chamber size	720 x 520 x 190 mm (W x D x H)
Length of sealing bars, crosswise	2 x 510 mm
Usable chamber width	600 mm
Cycle performance	2-3 cycles/min. depending on product size and required vacuum
Control system	IGT- <i>standard</i> ; monochrome TFT- screen with graphical user interface
Vacuum pump	63 m ³ /h integrated (100 m ³ /h on request)
Optional features	Gas supply, Soft-Air, double seam sealing, special voltage, single phase for 63 m ³ /h pump, slanted insert



WEBOMATIC®

Maschinenfabrik GmbH
Hansastr. 119
44866 Bochum/Germany

Telephone +49 (0) 2327-3099-0
Telefax +49 (0) 2327-3099-29
info@webomatic.de
www.webomatic.de